

# CSP-200IR Digital CCD Color Dome Camera

1/3-INCH, HIGH RESOLUTION, WEATHER-PROOF, VANDAL-PROOF, INFRARED

## Product Features

- Sony Super HAD™ Technology
- 1/3-Inch Format CCD Sensor
- Digital Signal Processing
- 480 Max TV Lines Resolution
- IP55 Weatherproof Rating
- 60 Feet Zero Lux Illumination
- UL Listed Vandal-proof
- Compact Housing



The **CSP-200IR** is an extremely durable, high resolution, infrared, color dome camera, providing a tamper resistant outdoor housing for any indoor/outdoor application.

The **CSP-200IR** features a Sony Super HAD™ 480 line, CCD sensor providing excellent color reproduction and remarkable sensitivity in zero lux environments.

The camera's 20-LED array of infrared illuminators can easily distinguish objects at a distance of 60 feet and beyond.

The **CSP-200IR** features an infinite-axis mount option making 90° wall mounting a breeze.

The aluminum cast structure and IP 55 weatherproof rated housing protects the camera during rain, sleet, and snow, while the armor design and crush resistant glass coating deters vandalism and ensures effective surveillance.

The non-intrusive, discreet housing is ideal for retail or public installs. Compact and simple design allows for a quick installation.

The **CSP-200IR** simple design guarantees efficient installation and service. The high resolution Sony Super HAD™ CCD gives the camera excellent, crisp images by day and noise free images in low lux environments. An excellent entry level vandal infrared dome for any installation.

## MODELS

CSP-200IR

High resolution digital color CCD dome camera with IR. 480 TVL, 12VDC, NTSC.

CSP-100IR

Normal resolution digital color CCD dome camera with IR. 420 TVL, 12VDC, NTSC.

## CAMERA

Sensor Type	1/3-inch Sony Super HAD™ CCD
Scanning System	2:1 Interlace
Horizontal Resolution	480 TV Line
Iris Control	Auto
Focus Control	Manual
Auto Iris	A.E.S.
Minimum Illumination	0 lux (IR On)
IR Range	25M 45°
LED Quantity	20
S/N Ratio	>50dB
Automatic Gain Control	Yes
Automatic White Balance	Yes
Electronic Shutter Speed	1/60 - 1/100,000 second
Gamma Correction	0.45
Signal Processing	Digital Signal Processing (DSP)
Video Output	1.0Vp-p(Sync, Negative), 75 ohms

## ELECTRICAL

Power Requirements	Regulated 12V DC
Power Consumption	300mA
Power Connector	2.1x 5.5, center positive
Video Connector	BNC

## MECHANICAL

Lens Type	3.6mm fixed
-----------	-------------

## ENVIRONMENTAL

Operating Temperature	-4° to 122°F (-20° to 50°C)
Storage Temperature	-4° to 131°F (-20° to 55°C)
Operating Humidity	90% RH Max.

## PHYSICAL

Dimensions	70(H) x 94(D)mm
Weight	1.1 lb (0.5 kg) approx.
Shipping Weight	1.25 lbs (0.57 kg) approx.

## RECOMMENDED POWER SUPPLIES

DSA	Power for one camera, 12V DC 1.25A
PS-4DC	Multi-output, 4ch, 12V DC 400mA
DPS-12D	Multi-output, 9ch, 12V DC 800mA
HPS-12D16	Multi-output, 16ch, 12V DC 800mA

## OPTIONAL ACCESSORIES

N/A

